

## 产品规格书

### Specifcation of products

产品名称:三相整流桥模块

产品型号: MDS500A-T18


浙江世菱半导体有限公司  
ZHEJIANG SHILING SEMICONDUCTOR CO.,LTD.

地址: 浙江省 丽水市 莲都区  
电话: (0578) 3012571 3615078  
传真: (0578) 3611180  
邮编: 323000  
E-mail: smrshiling01@163.com  
Http://www.smrshiling.com

拟制	审核	核准
林益龙	曹剑龙	宗瑞

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T <sub>j</sub> (°C)	VALUE			UNIT
				Min	Type	Max	
I <sub>o</sub>	DC output current	Three-phase full wave rectifying circuit, T <sub>C</sub> =100°C	150			500	A
V <sub>RRM</sub>	Repetitive peak reverse voltage	V <sub>RRM</sub> tp=10ms V <sub>RSM</sub> = V <sub>DRM</sub> &V <sub>RRM</sub> +200V	150		1600		V
I <sub>RRM</sub>	Repetitive peak current	at V <sub>RRM</sub>	150			15	mA
I <sub>FSM</sub>	Surge forward current	10ms half sine wave	150			8.0	KA
I <sup>2</sup> t	I <sup>2</sup> T for fusing coordination	V <sub>R</sub> =0.6V <sub>RRM</sub>					320
V <sub>FO</sub>	Threshold voltage		150			0.80	V
r <sub>F</sub>	Forward slop resistance						1.05
V <sub>FM</sub>	Peak forward voltage	I <sub>FM</sub> =500A	25			1.37	V
R <sub>th(j-c)</sub>	Thermal resistance Junction to heatsink	Single side cooled				0.06	°C /W
V <sub>iso</sub>	Isolation voltage	50Hz, R.M.S, t=1min, I <sub>iso</sub> : 1mA (max)		2500			V
F <sub>m</sub>	Terminal connection torque (M6)				5.0		N·m
	Terminal connection torque (M8)				7.0		N·m
	Mounting torque(M10)				9.0		N·m
T <sub>stg</sub>	Stored temperature			-40		125	°C
W <sub>t</sub>	Weight				1050		g
Outline							

### OUTLINE DRAWING & CIRCUIT DIAGRAM



### Rating and Characteristic




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

## Outside Dimension

