

产品规格书

Specifcation of products

产品名称:肖特基二极管

产品型号:MBDC200U2NT26C

浙江世菱半导体有限公司
ZHEJIANG SHILING SEMICONDUCTOR CO.,LTD.

地址:浙江省 丽水市 莲都区

电话:(0578) 3615066

邮编: 323000

E-mail:smrshiling12@163.com

Http://www.smrshiling.com


拟制	审核	核准
蓝少波	陈一凡	曹剑龙

PRODUCT FEATURES

- Ultrafast Reverse Recovery Time
- Soft Reverse Recovery Characteristics
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Inductance Package

APPLICATION S

- Inversion Welder
- Uninterruptible Power Supply (UPS)
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- Power Factor Correction (PFC) Circuit



ABSOLUTE MAXIMUM RATINGS

T_C=25℃ unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
V _R	Maximum D.C. Reverse Voltage		200	V
V _{RRM}	Maximum Repetitive Reverse Voltage		200	V
I _{F(AV)}	Average Forward Current	T _C =100℃, Per Diode	200	A
		T _C =100℃, Per Moudle	400	A
		T _C =100℃, 20KHz, Per Moudle	280	A
I _{F(RMS)}	RMS Forward Current	T _C =100℃, Per Diode	280	A
I _{FSM}	Non-Repetitive Surge Forward Current	1/2 Cycle, 60Hz, Sine	4000	A
I ² t	I ² t (For Fusing)	T _J =45℃, t=8.3ms, 60Hz, Sine	11200	A ² s
P _D	Power Dissipation		525	W
T _J	Junction Temperature		-40 to +150	℃
T _{STG}	Storage Temperature Range		-40 to +125	℃
Torque	Module-to-Sink	Recommended (M6)	3~5	N.m
Torque	Module Electrodes	Recommended (M6)	3~5	N.m
R _{θJC}	Thermal Resistance	Junction-to-Case	0.20	℃/W
Weight			100	g

ELECTRICAL CHARACTERISTICS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=200\text{V}$	--	--	0.2	mA
		$V_R=200\text{V}, T_J=125^{\circ}\text{C}$	--	--	2	mA
V_F	Forward Voltage	$I_F=200\text{A}$	--	0.90	--	V
		$I_F=200\text{A}, T_J=125^{\circ}\text{C}$	--	0.70	--	V




Figure1. Forward Voltage Drop vs Forward Current




Figure2. Reverse Recovery Charge vs di_F/dt




Figure3. Reverse Recovery Current vs di_F/dt






Figure4. Dynamic Parameters vs Junction Temperature



Package Outline



Dimensions (mm)