

产品规格书

Specifcation of products

产品名称：快恢复二极管

产品型号：MURP60060CT

浙江世菱半导体有限公司
ZHEJIANG SHILING SEMICONDUCTOR CO.,LTD.

地址：浙江省 丽水市 莲都区

电话：（0578）3615066

邮编：323000

E-mail:smrshiling12@163.com

Http://www.smrshiling.com

拟制	审核	核准
蓝少波	陈一凡	曹剑龙

Ultra-Fast Soft Recovery Diode Module

Description

Ultra-FRD module devices are optimized to reduce losses and EMI/RFI in high frequency power conditioning electrical systems. These diode modules are ideally suited for power converters, motors drives and other applications where switching losses are significant portion of the total losses.

Features


- Repetitive Reverse Voltage : $V_{RRM} = 60V$
- Low Forward Voltage Drop : $V_F(\text{typ.}) = 0.9V$
- Average Forward Current : $I_F(\text{AV.}) = 600A$ @ $T_c = 125^\circ C$
- Ultra-Fast Reverse Recovery Time : $t_{rr}(\text{typ.}) = 65 \text{ ns}$
- Extensive Characterization of Recovery Parameters
- Reduced EMI and RFI
- Non Isolation Type Package

Applications

Motor Drives, Free wheel use, High Power Converters, Welders, Various Switching and Telecommunication Power Supply

Equivalent Circuit and Package

Equivalent Circuit



Package



Please see the package Out line information

Absolute Maximum Ratings @ $T_j = 25^\circ C$ (Per Leg)


Symbol	Parameter	Conditions	Ratings	Unit
V_{RRM}	Repetitive Peak Reverse Voltage		60	V
$V_{R(DC)}$	Reverse DC Voltage		30	V
$I_{F(AV)}$	Average Forward Current @ $T_c = 25^\circ C$ @ $T_c = 100^\circ C$	Resistive Load	1000 600	A A
I_{FSM}	Surge (non-repetitive) Forward Current	One Half Cycle at 60Hz, Peak Value	4500	A
I^2_t	I^2t for Fusing	Value for One Cycle Current, $t_w = 8.3ms, T_j = 25^\circ C$ Start	175×10^3	$A^2 s$
T_j	Junction Temperature		$-40 \sim 125$	$^\circ C$
T_{stg}	Storage Temperature		$-40 \sim 125$	$^\circ C$
P_d	Maximum Power Dissipation		980	W
—	Mounting Torque		5.0	N.m
—	Terminal Torque		5.0	N.m

Thermal Characteristics

Symbol	Parameter	Conditions	Values			Unit
			Min.	Typ.	Max.	
$R_{th(j-c)}$	Thermal Resistance	Junction to Case	-	-	0.10	°C/W

Electrical Characteristics @ $T_J=25^{\circ}\text{C}$ (unless otherwise specified)

Symbol	Parameter	Conditions	Values			Unit
			Min.	Typ.	Max.	
V_R	Cathode Anode Breakdown Voltage	$I_R = 100\mu\text{A}$	100	-	-	V
V_{FM}	Maximum Forward Voltage	$I_{FM} = 600\text{A}$, $T_c = 25^{\circ}\text{C}$	-	0.9	1.0	V
		$I_{FM} = 600\text{A}$, $T_c = 100^{\circ}\text{C}$	-	0.7	0.8	V
I_{RRM}	Repetitive Peak Reverse Current	$T_C = 100^{\circ}\text{C}$, V_{RRM} applied	-	-	10.0	mA
t_{rr}	Reverse Recovery Time	$I_{FM} = 300\text{A}$, $V_R = 150\text{V}$ $di/dt = -100\text{A}/\mu\text{s}$ $T_C = 25^{\circ}\text{C}$	-	65	70	ns
		$T_C = 100^{\circ}\text{C}$	-	100	-	ns



Performance Curves




Fig. 1 : Typical Forward Voltage Drop vs. Instantaneous Forward Current




Fig. 2 : Typical Reverse Recovery Time vs. $-di/dt$




Fig. 3 : Transient Thermal Impedance (Z_{thjc}) Characteristics




Fig. 4 : Forward Current Derating Curve